


**MOTOROLA WIRELESS BROADBAND**

# Mesh Wide Area Network IAP 4300

## Two Radio Meshed WiFi Network with 4.9GHz for Public Safety


**Software Highlights**

The MWAN IAP 4300 offers a multitude of software features for enhancing your network experience. With Peer-to-Peer Communication Blocking ISPs (Internet Service Providers) now have an effective way to manage billing applications and client tracking scenarios. With the combination of the IAP 4300's VLAN support and standard 802.11e QoS, ISPs can create differentiated services that will allow them to offer tiered packages. Finally, historical, comprehensive statistics are now available for future reference and review.

**Mesh Wide Area Network**

The Mesh Wide Area Network (MWAN) product series makes wireless cities a reality with robust and future-proof wireless broadband technologies. Whether providing wireless access to a campus, business, neighborhood or city, MWAN delivers real-time data to your first responders, residents, employees, and customers, enabling vital wireless broadband applications.

**Dual Mesh Operation**

Public safety agencies require data traffic that is separate and secure from public access. MWAN 4300 products operate as a dual mesh, with the licensed 4.9GHz system providing client access to first responders, as well as meshed backhaul to create a private and secure network. Furthermore, the IAP 4300's 10MHz and 20MHz channel support for 4.9GHz allows channel flexibility within the Public Safety Network. The 2.4GHz system provides meshed radio links, and client access to business and residential users, keeping the two systems separated.

**Proven Mesh Routing**

MWAN IAP 4300 leverages MeshConnex™ routing technology, using real-time congestion management and link control to automatically select the best data route on a per-request basis. This dramatically reduces hop latency, to better deliver real-time voice and multimedia services. Today, MeshConnex powers large-scale Motorola mesh networks of more than 1,000 nodes.

**Carrier-Class Security**

The IAP 4300 supports complete, end-to-end security. It provides WEP, WPA and WPA2 encryption on client access. Motorola's own Secure Mesh ensures the highest data security within the meshed WiFi network. Finally, users can create access lists that can block particular clients from accessing the network.

**Compact Form Factor**

The small profile, light weight form factor, and slim-line aesthetics increase mounting location flexibility and community acceptance.

**Advanced Network Management**

The 4300 series utilizes Motorola's One Point Wireless Manager to manage and visualize a multitude of capabilities for small to large networks and all of these capabilities are controllable from a single suite of software. By completing one profile, a large number of devices can be configured easily, reducing the time required to provision individual devices and complete on-going adjustments. Once the network is up and running, the Wireless Manager is a flexible and powerful tool that monitors the health of the network's components for quick detection and resolution of problems that can impact network performance and user satisfaction.

**Flexible & Adaptable Gateways**

Every 4300 series access point unit is capable of being an Intelligent Access Point (IAP) or Mesh Wireless Router (MWR), reducing the cost of storing excess inventory and simplifying deployment. Additionally, gateway nodes immediately adapt to backhaul loss by becoming wireless routers, routing traffic to an alternate gateway in the network. This automatic, self-healing ability minimizes service interruptions and ensures continuous connectivity.

**Quality of Service (QoS)**

Delay-sensitive applications like video and voice services require different data priorities. The IAP 4300 supports IEEE 802.11e based traffic prioritization. It constantly monitors node congestion, and automatically tunes its QoS parameters to optimize route selections to support latency sensitive applications.

**Motorola, Your End-to-End Solution Provider**

Motorola's wireless broadband portfolio offers an array of access and backhaul technologies for complete end-to-end wireless initiatives. Motorola's Fixed Point-to-Multipoint and Point-to-Point solutions provide reliable, high-capacity Internet backhaul links to Motorola's mesh networks. MeshPlanner and MeshScanner enable detailed network planning and optimization capabilities. Additionally, Motorola's ecosystem of applications offers a wide range of validated solutions to garner multiple benefits from your wireless network.

SPECIFICATION SHEET

MWAN IAP 4300  
Two Radio Meshed WiFi Network  
with 4.9GHz for Public Safety

**Benefits**

- Best-in-class radio performance
- Reliable coverage
- Best-in-class throughput
- Robust security

**Motorola Wireless Broadband**

Motorola's comprehensive portfolio of reliable and cost-effective wireless broadband solutions together with our EWLAN solutions provide and extend coverage both indoors and outdoors. The Motorola Wireless Broadband portfolio offers high-speed Point-to-Point, Point-to-Multipoint, Mesh, Wi-Fi and WiMAX networks that support data, voice and video communications, enabling a broad range of fixed and mobile applications for public and private systems. With Motorola's innovative software solutions, customers can design, deploy and manage a broadband network, maximizing uptime and reliability while lowering installation costs.

MWAN IAP 4300 • 4300-49 RADIO CHARACTERISTICS	
IEEE 802.11b/g Radio (20MHz Channel)	2.400 to 2.483GHz
IEEE 802.11a Radio (10MHz and 20MHz Channel)	4.940 to 4.990GHz
RF Modulation	CCK (802.11b), OFDM (802.11a/g)
Transmit Power (Maximum)	35dBm EIRP (802.11b/g), 34 dBm EIRP (802.11a) • Settable in 1dB increments
Receive Sensitivity	802.11b: -92dBm @ 11 Mbps to -100dBm @ 1 Mbps 802.11g: -78dBm @ 54 Mbps to -95dBm @ 6 Mbps 802.11a: -77dBm @ 27 Mbps to -93dBm @ 3 Mbps 802.11j: -78dBm @ 5.4 Mbps to -95dBm @ 6 Mbps
Antenna Type	N-Type • Two (2) omnidirectional: 8dBi for 2.4GHz and 11dBi for 4.9GHz
ROUTING	
Technology	MeshConnex routing with Layer 1 situational-awareness
Protocol	Patented, Layer 2, hybrid proactive/reactive routing
NETWORK	
Network Management Software	SNMPv1, SNMPv2c or secure SNMPv3 via One Point Wireless Manager Web Interface via HTTPS (SSL) 802.11 and MWAN MIBs
Network Interface	Weatherized 10/100 Base-T Ethernet (RJ-45) port with surge suppression
Network Segmentation	16 VAPs (Multiple SSIDs with VLAN mapping)
Quality of Service (QoS)	802.11e, weighted fair queuing and IP precedence bits (ToS) supported via DSCP
SECURITY	
Client Encryption Support	WEP, WPA (TKIP) and WPA2 (AES, 802.11i)
Intra-Mesh Encryption	Secure Mesh with AES
Authentication	802.1X (Infrastructure/Client) and MAC address hardware authentication
TCP/IP Filtering	Broadcast storm and port filtering
POWER	
Power Input	90-264 VAC (with +/- 20% variation at 47-63Hz) or Optional 10.8-14VDC (2.5A Max)
Power Connector	Weatherized NEMA 5-15 power cord • 12 ft (3.66m)
Power Consumption	15W to 30W (with PoE device)
Power over Ethernet (PoE)	Support for Point-to-Multipoint PoE, or 802.3af Standard PoE device
PHYSICAL	
Dimensions	9"x 6"x 3.5" (23.1cm x 15.2cm x 8.9cm) • 189in <sup>3</sup> (3097cm <sup>3</sup> )
Weight	4.5 lbs (2.04kg)
Packaging	Outdoor, all-weather enclosure (NEMA 4 / IP65)
Mounting	3" (7.62cm) diameter post mounting
ENVIRONMENTAL & REGULATORY	
Temperature Range	-30 to 60 °C (-22 to 140 °F)
Humidity	0 to 95%, non-condensing at 50 °C (122 °F)
Regulatory Certifications	FCC Part 15 & 90, CE, MET Mark / CSA / UL, RoHS / CMM / WEEE, Industry Canada
AVAILABLE OPTIONS & ACCESSORIES	
Mounting	Lamp post mount bracket assembly
Antennas	4 or 6dBi omnidirectional for 2.4GHz
Power Plug Adapters	AC photo cell adapter and US, EU, and AU Power Plug Adapters
Power Over Ethernet (PoE) Adapters	Point-to-Multipoint Connect or IEEE 802.3af PoE

ONE YEAR PARTS & LABOR WARRANTY



**MOTOROLA**

Motorola, Inc. [www.motorola.com/mesh](http://www.motorola.com/mesh)

The information presented herein is to the best of our knowledge true and accurate. No warranty or guarantee expressed or implied is made regarding the capacity, performance or suitability of any product. Product specifications subject to change without notice.

MEA, MeshConnex and Hop-by-Hop Security are trademarks or registered trademarks of Motorola, Inc. MOTOROLA and the Stylized M Logo are registered in the U.S. Patent and Trademark Office. All other product or service names are the property of their registered owners. © Motorola, Inc. 2010 G3-25-107